

ALUMINIUM TUBULAR CABLE CONNECTORS

TUBULAR CABLE CONNECTOR AS PER 12-SDMS-02



PESSRL Aluminium rod lug "For non-tension connections of aluminium conductors to DIN EN 60228 and aluminium cables to DIN EN 50182

- Infused with contact grease to enhance crimp characteristics to their optimal performance.
- Item identification on cable Connector
- Easy to process due to crimp markings.
- Simple and safe processing due to center punch mark
- Material - E-copper as per EN 13600
- Dimension as per 12-SDMS-02 REV:06 or DIN 46267, PART 2

Nominal Cross Section mm ²	PESSRL CAT NO.	d1	d4	l
10	PESAC-10	5	10	55
16	PESAC-16	5.8	12	55
25	PESAC-25	6.8	12	70
35	PESAC-35	8	14	85
50	PESAC-50	9.8	16	85
70	PESAC-70	11.2	18.5	105
95	PESAC-95	13.2	22	105
120	PESAC-120	14.7	23	105
150	PESAC-150	16.3	25	125
185	PESAC-185	18.3	28.5	125
240	PESAC-240	21	32	145
300	PESAC-300	23.3	34	145
400	PESAC-400	26	38	210
500	PESAC-500	29	44	210