

MECHANICAL CONNECTOR SCREW CONNECTOR TYPE-2



PESSRL MECHANICAL CONNECTOR: To establish connections between different types and materials of conductors, such as those specified in DIN EN 60228 Cl. 1 and 2.

- Perfect for linking conductor cross-sections, whether identical or different.
- Ensures dependable processing through cable insertion control, preventing contact between dissimilar materials.
- Material: Highly tensile aluminium alloy
- Screw: Aluminium alloy
- Surface: Tin Plated

PESSRL CAT NO.	AL in MM ²				Cu in MM ²			Outer Diameter	Number of Bolt	Share-off Torque	Wrench Size
	Round stranded	Sector Stranded	Round Solid	Sector Solid	Round stranded	Sector Stranded	Round Solid				
PESC-10-35/2L	10-35	10-25	10-35	10-25	10-16	10-16	10-16	16	2	8	9
PESC-25-50/2L	25-50	25-35	25-50	25-35	25-35	25-35	25-35	18	2	12	10
PESC-50-95/2L	50-95	50-70	50-95	50-70	50	50	50	22	2	22	13
PESC-120-185/2L	120-185	120-150	120-185	120-150	120	120	120	30	2	40	17
PESC-240-300/4L	240-300	240	240-300	240	240	240	240	36	4	55	22