


COPPER RING CABLE LUG

CRIMPING TYPE INSULATED TINNED COPPER RING CABLE TERMINAL END



PESSRL Ring Type Light Duty Insulated Cable Lugs are commonly used in electrical panels, control systems, telecommunications, and automotive applications where safety and reliability are paramount.


- All the terminals are tin plated to avoid oxidation and to achieve maximum corrosion protection.
- The insulation sleeve, often made from PVC, protects against moisture, chemicals, and abrasion, ensuring long-lasting performance and reliability in diverse environments.
- Material: Copper (ETP) IS 1897
- Finish: Electro tin to BS 1872 (1984)
- Color coding of insulation sleeve

1.5 2.5 4-6


Nominal Cross Section mm ²	PESSRL CAT NO.	Size of Bolt Die	A	D	F	B	J	J-1	COLOR
1.5	PESRI-7053	1.5	2.6	1.6	0.8	5	14	10	Red
	PESRI-7054	1.5	3.2	1.6	0.8	5	14	10	Red
	PESRI-7055	1.5	3.7	1.6	0.8	5	14	10	Red
	PESRI-7056	1.5	4.2	1.6	0.8	5	14	10	Red
	PESRI-7058	1.5	3.7	1.6	0.8	5	13	10	Red
	PESRI-7059	1.5	4.2	1.6	0.8	5	13	10	Red
	PESRI-7065	1.5	5.2	1.6	0.8	5	18	10	Red
	PESRI-7066	1.5	6.4	1.6	0.8	5	18	10	Red
	PESRI-7061	1.5	4.2	1.6	0.8	5	16	10	Red
	PESRI-7062	1.5	5.2	1.6	0.8	5	16	10	Red
	PESRI-7052	1.5	2.2	1.6	0.8	5	14	10	Red
	PESRI-7057	1.5	3.2	1.6	0.8	5	13	10	Red
	PESRI-7064	1.5	4.2	1.6	0.8	5	18	10	Red
	PESRI-7067	1.5	6.4	1.6	0.8	5	18	10	Red
	PESRI-7060	1.5	3.2	1.6	0.8	5	16	10	Red
	PESRI-7063	1.5	4.2	1.6	0.8	5	14.5	10	Red
	PESRI-7069	2.5	3.7	2.3	0.8	5	12.7	10	Blue
	PESRI-7071	2.5	4.2	2.3	0.8	5	16	10	Blue
2.5	PESRI-7072	2.5	5.2	2.3	0.8	5	16	10	Blue
	PESRI-7074	2.5	6.4	2.3	0.8	5	18	10	Blue
	PESRI-7076	2.5	6.4	2.3	0.8	5	22	10	Blue
	PESRI-7077	2.5	8.2	2.3	0.8	5	22	10	Blue
	PESRI-7079	2.5	8.2	2.3	0.8	5	25	10	Blue
	PESRI-7080	2.5	10.2	2.3	0.8	5	25	10	Blue
	PESRI-7082	2.5	12.7	2.3	0.8	5	29	10	Blue
	PESRI-7068	2.5	3.2	2.3	0.8	5	12.7	10	Blue
	PESRI-7070	2.5	3.7	2.3	0.8	5	16	10	Blue
	PESRI-7073	2.5	5.2	2.3	0.8	5	18	10	Blue
	PESRI-7075	2.5	5.2	2.3	0.8	5	22	10	Blue

COPPER RING CABLE LUG

CRIMPING TYPE INSULATED TINNED COPPER RING CABLE TERMINAL END



PESSRL Ring Type Light Duty Cable Lugs are commonly used in electrical panels, control systems, telecommunications, and automotive applications where safety and reliability are paramount.



- All the terminals are tin plated to avoid oxidation and to achieve maximum corrosion protection.
- The insulation sleeve, often made from PVC, protects against moisture, chemicals, and abrasion, ensuring long-lasting performance and reliability in diverse environments.
- Material: Copper (ETP) IS 1897
- Finish: Electro tin to BS 1872 (1984)
- Color coding of insulation sleeve

1.5 2.5 4-6

Nominal Cross Section mm ²	PESSRL CAT NO.	Size of Bolt Die	A	D	F	B	J	J-1	COLOR
2.5	PESRI-7078	2.5	6.4	2.3	0.8	5	25	10	
	PESRI-7081	2.5	10.2	2.3	0.8	5	29	10	
	PESRI-7086	4-6	5.2	3.5	1	6	19	14	
4-6	PESRI-7089	4-6	6.4	3.5	1	6	20	14	
	PESRI-7090	4-6	8.2	3.5	1	6	20	14	
	PESRI-7092	4-6	6.4	3.5	1	6	22	14	
	PESRI-7094	4-6	8.2	3.5	1	6	25.5	14	
	PESRI-7095	4-6	9.7	3.5	1	6	25.5	14	
	PESRI-7097	4-6	10.2	3.5	1	6	30	14	
	PESRI-7099	4-6	10.2	3.5	1	6	30	14	
	PESRI-7100	4-6	12.7	3.5	1	6	30	14	
	PESRI-7084	4-6	5.2	3.5	1	6	17	14	
	PESRI-7085	4-6	4.2	3.5	1	6	19	14	
	PESRI-7088	4-6	5.2	3.5	1	6	20	14	
	PESRI-7091	4-6	5.2	3.5	1	6	22	14	
	PESRI-7093	4-6	6.4	3.5	1	6	25.5	14	
	PESRI-7096	4-6	8.2	3.5	1	6	30	14	
	PESRI-7098	4-6	8.2	3.5	1	6	30	14	
	PESRI-7083	4-6	4.2	3.5	1	6	17	14	
	PESRI-7087	4-6	5.2	3.5	1	6	22	14	